

MINNESOTA DEPARTMENT OF TRANSPORTATION RIGHT OF WAY PLAT NO. 20-24

STATE PROJECT NO. 2006(56-56-21-1)
IN THE WEST HALF OF SECTION 29, T. 108 N., R. 17 W., AND
THE EAST HALF OF SECTION 30, T. 108 N., R. 17 W.
DODGE COUNTY, MINNESOTA

THE COMMISSIONER OF TRANSPORTATION IS HEREBY DESIGNATING THE DEFINITE
LOCATION OF TRUNK HIGHWAY NO. 56 FROM DODGE CENTER TO THE WEST JUNCTION OF
TRUNK HIGHWAY NO. 14

RIGHT OF WAY IN SECTION 29							
PARCEL	OWNER	LOCATION	TORREN'S CERTIFICATE NO.	NEW T.H. R/W ACRES (MORE OR LESS)	TEMPORARY EASEMENT (MORE OR LESS)	BUILDING REMOVAL EASEMENT	PERMANENT R/W INTEREST
222	LEROY W. HARMS	W1/2NW1/4		0.66			FEE
222A	FIRST BAPTIST CHURCH OF WEST CONCORD	NW1/4NW1/4		0.31			FEE
225	E.L. LANGWORTHY AND CO.	W1/2SW1/4		1.06			FEE
225A	JOSEPH M. KVAM	W1/2SW1/4		0.24			FEE
RIGHT OF WAY IN SECTION 30							
323	FRED W. STONE	E1/2NE1/4		0.69			FEE
323A	ROBERT W. STONE	NE1/4NE1/4		0.10	0.09	12-1-88	FEE
224	CLAIR L. DUTTON	SE1/4SE1/4		0.37			FEE
224A	WILLIAM V. SMITH	NE1/4SE1/4		0.32			FEE
224B	TIMOTHY CHLADEK	NE1/4SE1/4		0.04	0.03	12-1-88	FEE

As shown on this plat prepared by the Minnesota Department of Transportation is hereby certified as the official plat of that portion of road T.H. 56 within the designated portion of Sections 29 & 30 and the Commissioner's Order therefor pursuant to Minnesota Statutes, sections 161.15 subd.2, section 168.14 Subd.1, and section 168.065.

Commissioner's Order No.	Location	Nature of Interest
68021	PLATS 20-23 THRU 20-29	Definite location, width, access, temporary easement and building removal easement.

Recommended for Certification: _____ Certified: _____

Richard P. Brown
Commissioner of Transportation

By: *[Signature]* Date: 10-28-83
By: *[Signature]* Date: 10-28-83

R.J. Orndorff
Director of R/W Operations

By: *[Signature]* Date: 11-10-83
By: *[Signature]* Date: 11-10-83

I hereby certify that this plat was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the Law of the State of Minnesota; that this plat meets requirements of Minnesota Statutes, section 161.15 Subd.2, section 168.14 Subd.1 and section 168.065; that parcel ownerships are correctly described and delineated on the plat and that the proposed right-of-way boundary lines are correctly designated on the plat.

I hereby certify that this plat was surveyed by me or under my direct supervision and that I am a duly Registered Land Surveyor under the Law of the State of Minnesota; that all measurements are correctly shown on this plat and that all monuments have been correctly placed as shown on this plat.


Certified by: *[Signature]* 10460 10-28-83
Registered Land Surveyor
Office of Surveying & Mapping

Certified by: *[Signature]* 11527 11-10-83
Registered Land Surveyor
MVDOT District Office

PLAT BOUNDARY DATA		
POINT	DISTANCE	AZIMUTH
NE 30-B2311	151.39'	90° 40' 58"
B2311-B1	33.00'	180° 40' 58"
B1-B2	103.90'	224° 31' 49"
B2-B3	2238.61'	178° 22' 39"
B3-B4	312.60'	178° 30' 28"
B4-B5	308.05'	178° 46' 00"
B5-B6	938.35'	178° 53' 42"
B6-B7	10.00'	268° 54' 18"
B7-B8	280.55'	178° 53' 42"
B8-B9	10.00'	88° 53' 42"
B9-B10	720.98'	178° 53' 42"
B10-B2411	400.21'	178° 03' 56"
B2411-B2412	10.00'	270° 14' 59"
B2412-NE 31	64.30'	270° 14' 59"
NE 31-B2414	150.72'	269° 12' 47"
B2414-B15	10.11'	359° 15' 15"
B15-B16	106.30'	44° 04' 06"
B16-B17	312.57'	359° 01' 42"
B17-B18	949.16'	358° 53' 42"
B18-B19	10.00'	88° 54' 18"
B19-B20	365.00'	358° 53' 42"
B20-B21	10.00'	268° 54' 18"
B21-B22	625.72'	358° 53' 42"
B22-B23	310.38'	358° 45' 55"
B23-B24	308.91'	358° 30' 23"
B24-B25	1690.50'	358° 22' 39"
B25-B26	10.00'	89° 01' 35"
B26-B27	577.00'	358° 22' 39"
B27-B28	71.11'	313° 42' 05"
B28-B29	35.75'	269° 01' 35"
B29-B2312	33.00'	359° 01' 35"
B2312-NE 30	150.38'	89° 01' 35"

- SURVEY STANDARDS**
- The plat values, azimuths and distances, are based on the project control survey system.
 - The boundary monuments shown on this plat have been field checked for location. The standard deviation for the monument position is 0.1' ft.
 - The state plane coordinate shown on one monument are based on ties to national control monuments.
 - Certificates of Location have been filed at the County Recorder's Office and/or the County Surveyor's Office for the section corner monuments shown on this plat.
 - For details of this survey contact the Surveying and Mapping Section at the Minnesota Department of Transportation, ROCHESTER, Name of District _____

AZIMUTH ORIENTATION AND GRID CONVERSION
Plat azimuths are oriented to Minnesota State Plane Coordinate System with 8 degree 8 minutes 8 seconds being GRID NORTH.
Plat distances are ground lengths and can be converted to Minnesota State Plane Grid lengths by multiplying Plat distances by 0.9999003



CONVENTIONAL SYMBOLS

- | | | |
|--------------------------|--|---------|
| Section Line | Building Removal Easement | B, R, E |
| Quarter Line | R/W Parcel Number | 3 |
| Sixteenth Line | Access Control | ○ |
| Property Line | Access Opening | ○ |
| R/W Boundary | Cast Iron Monument or 2x2 D.O.T. Iron Pipe with Aluminum Cap | ⊙ |
| Existing D.O.T. R/W Line | 3/4" D.O.T. Iron Pipe | ⊙ |
| And Other Road R/W's | Other Iron Monument | ⊙ |
| Private Easement | Concrete or Stone Monument | ⊙ |
| Temporary Easement | R/W Boundary Corner | ⊙ |

DISTANCES SHOWN TO FEET 66.68 ET/CAVE EXTRINSIC VALUES.

DOC. NO. 58711

OFFICE OF COUNTY RECORDER
DODGE COUNTY, MINN.

I HEREBY CERTIFY THAT THIS PLAT
HAS BEEN FILED IN THIS OFFICE
AT 2:00 CLOCK P.M. ON
DEC. 5, 1983

BOOK OF _____ PAGE _____

COUNTY RECORDER