


MINNESOTA DEPARTMENT OF TRANSPORTATION RIGHT OF WAY PLAT NO. 20-34

STATE PROJECT NO. 2002 (14-7)902
IN THE SOUTHWEST QUARTER OF SECTION 35, T. 107 N., R. 17 W.,
DODGE COUNTY, MINNESOTA

RIGHT OF WAY IN SECTION 35								
PARCEL	OWNER	LOCATION	TORRENS CERTIFICATE NO.	NEW T.N. R/W ACRES (MORE OR LESS)	TEMPORARY EASEMENT	BUILDING REMOVAL EASEMENT	EASEMENT EXPIRES ON	PERMANENT R/W INTEREST
9	CITY OF DODGE CENTER	S1/2SW1/4		5.74	0.29		12-01-04	FEE
10	HAROLD O. REHWALDT	S1/2SW1/4		17.62	0.83	0.17	12-01-00	FEE

PLAT BOUNDARY DATA		
POINT	DISTANCE	AZIMUTH
B3401-B3402	283.85'	180°01'37"
B3402-B3	1163.15'	270°17'10"
B3-B4	836.06'	259°55'48"
B4-B5	733.30'	239°32'02"
B5-B3406	450.00'	179°58'53"
B3406-NE 3	33.00'	270°07'36"
NE 3-B3407	1269.58'	359°58'53"
B3407-B3401	2645.22'	90°16'26"

RAILROAD SPIKE ABOVE CAST IRON MONUMENT AT QUARTER CORNER



MN/DOT CAST IRON CAP ON SQUARE STEEL MONUMENT AT QUARTER CORNER



1/2 INCH PIPE STAMPED RLS 10832 AT QUARTER CORNER

THE COMMISSIONER OF TRANSPORTATION IS HEREBY DESIGNATING THE DEFINITE LOCATION OF TRUNK HIGHWAY NO. 14 FROM THE JUNCTION OF COUNTY ROAD 1 TO 0.5 MILE EAST

as shown on this plat prepared by the State of Minnesota Department of Transportation is hereby certified as the official plat of that portion of said T.N. 14 within the designated portion of Section 35 and the Commissioner's Order therefor, pursuant to Minnesota Statutes, section 160.085, section 160.14 subd. 1, section 161.16 subd. 2, and section 161.18.

It is further ordered that it is necessary to acquire all trees, shrubs, grass, and herbage within the right of way of said Trunk Highway, and to keep and have the exclusive control of the same. It is further ordered that the right to erect and maintain temporary snow fences under Minnesota Statutes, Section 117.21 is hereby disclaimed on the land which will be involved.

Commissioner's Order No.	Location	Nature of Interest
82595	PLAT 20-34	Definite location, width, access, temporary easement and building removal easement.


Certified by James N. Dann Commissioner of Transportation
Merritt Linz 10-21-97
by Merritt Linz Date
Director, Office of Land Management

I hereby certify that this plat was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the Laws of the State of Minnesota; that this plat meets requirements of Minnesota Statutes, section 160.085, section 160.14 subd. 1, section 161.16 subd. 2, and section 161.18; that parcel ownerships are correctly described and delineated on the plat; and that the proposed right-of-way boundary lines are correctly designated on the plat.
Certified by Sharon Lober 11933 10-21-97
Registered Land Surveyor License No. Date
Office of Land Management

I hereby certify that this plat was surveyed by me or under my direct supervision and that I am a duly Registered Land Surveyor under the Laws of the State of Minnesota; that all measurements are correctly shown on this plat, and that all monuments have been correctly placed as shown on this plat.
Certified by Eugene A. Mandinger 21557 10-27-97
Registered Land Surveyor License No. Date
Mn/DOT District Office

C12-5

CAST IRON MONUMENT AT SECTION CORNER



DODGE COUNTY COORDINATES
X= 520,406.33
Y= 168,828.13
DATUM= NAD 1983

- SURVEY STANDARDS**
- The plat values, azimuths, and distances are based on the project control survey system.
 - The boundary monuments shown on this plat have been field checked for location. The standard deviation for the monument position is 0.10 foot.
 - The county coordinates shown on one monument are based on ties to national control monuments.
 - Certificates of Location have been filed at the County Recorder's Office and/or the County Surveyor's Office for the section corner monuments shown on this plat.
 - For details of this survey contact the Surveying and Mapping Section at the Minnesota Department of Transportation, ROCHESTER Name of District

AZIMUTH ORIENTATION AND GRID CONVERSION
Plat azimuths are oriented to the County Coordinate System with 0 degrees 0 minutes 0 seconds being "GRID NORTH". Plat distances are ground lengths.



CONVENTIONAL SYMBOLS

Section Line	Building Removal Easement	B. R. E.
Quarter Line	R/W Parcel Number	3
Sixteenth Line	Access Control	OPEN
Property Line	Access Opening	OPEN
R/W Boundary	Cast Iron Monument or 2"x2" D.O.T. Iron Pipe with Aluminum Cap	●
Existing D.O.T. R/W Line	3/4" D.O.T. Iron Pin	○
And Other Road R/W's	Other Iron Monument	○
Railroad R/W	Concrete or Stone Monument	□
Private Easement	Temporary Easement	T. E.
Temporary Easement	R/W Boundary Corner	●

DISTANCES SHOWN TO FEET (66, 80 ETC.) ARE EXACT VALUES.



1/2 INCH PIPE STAMPED RLS 10832 AT QUARTER CORNER

DOC. NO. 109913
OFFICE OF COUNTY RECORDER
DODGE COUNTY, MINN.
I HEREBY CERTIFY THAT THIS PLAT HAS BEEN FILED IN THIS OFFICE AT 9:30 O'CLOCK A.M. ON October 28, 1997 IN BOOK 8 OF PLATS, PAGE 46-B
COUNTY RECORDER